

NPS	DN	A	В	C	D	Е	F	G	nx Φ H	ISO5211	L	M	P	Q	X	Y
2"	50	52.6	142	32	80	96	70	90	4x φ 10	F7	43	9	120.65	4-5/8UNC	251.2	174
2.5"	65	64.4	155	32	89	116	70	90	4x φ 10	F7	46	9	139.7	4-5/8UNC	251.2	187
3"	80	78. 9	161	32	95	132	70	90	4x φ 10	F7	46	9	152. 4	4-5/8UNC	251.2	193
4"	100	104. 1	180	32	114	152	70	90	4x φ 10	F7	52	11	190.5	8-5/8UNC	251.2	212
5"	125	123. 4	193	32	127	182	70	90	4x φ 10	F7	56	14	215.9	8-3/4UNC	251.2	225
6"	150	155. 96	205	32	139	205	70	90	4x φ 10	F7	56	14	241.3	8-3/4UNC	251.2	237

HALF RING SS O-Ring EPDM Bush Nylon 6 5 LowerShaft SS420 UpperShaft 4 SS420 EPDM Seat Disc CF8M

DUCTILE IRON

DESCRIPCION

Body

PARTS

N□.

SIZE:	PRESSURE:	PN16 WEIG		Τ:	SCALE:		
DRFTER:	SPECIFICATION:	MAPLEF		TITLE: 2" TO 6" LT STYLE BUTTERFLY			
CHECKED BY:			DR	AWING NO.:	DATE:	$ \oplus $	



This certifies that

TIANJIN GREATWALL FLOW VALVE CO. LTD.

has had the undermentioned product(s) examined, tested and certified as being of an appropriate quality and standard as required in the Water Supply (Water Fittings) Regulations and Scottish Water Byelaws, subject to scheme requirements being met when installed.

Model Numbers

D71X-10/16-701/705-00 & D71X-10/16-702/706-00 BUTTERFLY VALVES: DN32-400

The certificate by itself is not evidence of a valid WRAS Approval. Confirmation of the current status of an approval must be obtained from the WRAS Approvals Directory (www.wras.co.uk/directory)

The product so mentioned will be valid until the end of:

March 2026

Certificate No.

2103018

lan Hughes, WRAS Approvals Manager