

## PRODUCT SPECIFICATIONS

## A21



COMMON INDUSTRY #	d	D	L	D1	L1
290	0.625	1.062	0.875	1.250	0.406
358	0.750	1.187	0.875	1.375	0.406
309	0.875	1.312	0.937	1.500	0.406
235	1.000	1.687	1.000	1.625	0.437
356	1.125	1.812	1.062	1.750	0.437
185	1.250	1.937	1.062	1.875	0.437
177	1.375	2.062	1.125	2.000	0.437
758	1.500	2.187	1.125	2.125	0.437
238	1.625	2.500	1.375	2.375	0.500
446	1.750	2.625	1.375	2.500	0.500
340	1.875	2.750	1.500	2.625	0.500
267	2.000	2.875	1.500	2.750	0.500
543	2.125	3.000	1.687	3.000	0.562
1679	2.250	3.125	1.687	3.125	0.562
268	2.375	3.250	1.812	3.250	0.562
2120	2.500	3.343	1.812	3.375	0.562
2625	2.625	3.500	1.937	3.375	0.625
836	2.750	3.750	1.937	3.500	0.625
270	2.875	3.875	2.062	3.750	0.625
1696	3.000	4.000	2.062	3.875	0.625

## Single Spring, Elastomer Bellows Seal



### Features and Benefits:

- Cost effective seal common to many process pumps
- Bellows design helps compensate for face wear
- Bi-directional
- Multiple face and elastomer choices
- Equivalent to John Crane Type 21, Pac-Seal Type 21, US Seal C head

### Standard Materials of Construction:

#### • Faces:

- Carbon Graphite (Resin Impregnated), Antimony-Impregnated Carbon, Silicon Carbide, Tungsten Carbide

#### • Elastomers:

- Buna, Viton®, Aflas®, Neoprene, EPDM

#### • Metallurgy:

- 304, 316, Monel

### Operating Limits:

- Pressure: 150 psi 10.3 Bar
- Temperature: -40°F to +400°F.

All industry standard "PS" numbers are available,

All seat styles available

Just provide us the "PS" number required or one used on previous orders

